

Overview of our staplers and nail guns

DGKD200091	DGKD200092	DGKD200098	DGKD200094	DGKD300046	DGKD300067	DGKD300068	DGKD300071
KLG 80-16	KLG 90-25	KLG 90-40	KLG 114-65	KNG 40/50	SNG-SK 50	PNG-PN 25	RNG RN 90

Application options							
Sheeting, insulation material	++						
Fabrics, leather	++						
Furniture rear panels	++	++	+		+		
Skirting boards					++	++	+
Wooden ceilings		+	++		++	+	
Tongue and groove boards/ panels		++	++		++	+	
Gypsum plasterboard/OSBs				++			+
Boxes, pallets			+	++	+	+	++
Trim strips, decorative elements					+	+	++
Window beads					+	+	++
Roof battens							++
Cladding							++
Timber frames and trestles							++

++ very well suited

+ well suited

Stapler and nail gun model overview

Model	Art. no.	Air requirement [l/impact]	Magazine capacity	Weight [kg]	Page in the catalogue
KLG 80-16	DGKD200091	0.3	157	0.87	200
KLG 90-25	DGKD200092	0.8	100	1.1	200
KLG 90-40 SYS	DGKD200098	0.8	100	1.1	200
KLG 114-65	DGKD200094	1.3	130	2.5	200
SNG-SK 50 SYS	DGKD300067	1.1	100	1.26	202
KNG 40/50 SYS	DGKD300046	1.1	100	1.1	202
PNG-PN 25 SYS	DGKD300068	0.3	102	0.95	203
RNG-RN 90	DGKD300071	2.9	63	3.3	204

Staplers and nail guns

For strong joints



Compact, lightweight design for easy handling and fatigue-free work



Rubber handle reduces vibrations and provides insulation against the cold



Simple and precise adjustment of the staple insertion depth with tool-free depth setting



User-friendly sliding mechanism on the magazine makes loading the staples easy



Example: Stapler KLG 114-65

Our extensive range of staplers and nail guns offers the perfect machine for every application and includes a wide selection of compatible nails and staples. They are used in upholstery and interior design, as well as in carpenter's and joiner's workshops.

Staplers and nail guns

Stapler

- Compact, lightweight design for easy operation and fatigue-free work
- Rubber handle reduces vibrations and provides insulation against the cold
- Staples reloaded easily with user-friendly loading device



KLG 80-16

- Long carrier for reaching awkward areas which are difficult to access
- Two-stage trigger prevents injuries caused by unintentional or accidental tool triggering
- For staples type 80, length 4-16 mm



KLG 90-25

- Contact release for quick, safe working progress
- Simple and precise adjustment of the staple insertion depth with tool-free depth setting
- For staples type 90, length 13-25 mm



KLG 90-40 SYS

- Contact release for quick, safe working progress
- Simple and precise adjustment of the staple insertion depth with tool-free depth setting
- For staples type 90, length 13-40 mm
- In a Systainer with safety glasses, 2000 staples, type 90, length 30 mm



KLG 114-65


- Set the trigger to single release or contact release for flexible working progress
- Simple and precise adjustment of the staple insertion depth with tool-free depth setting
- For staple type 114, up to 65 mm

Model	Art. no.	Air requirement (l/impact)	Working pressure (bar)	Magazine capacity	Weight (kg)
KLG 80-16	DGKD200091	0.3	4-7	157	0.87
KLG 90-25	DGKD200092	0.8	5-8	100	1.0
KLG 90-40 SYS	DGKD200098	0.8	5-8	100	1.1
KLG 114-65	DGKD200094	1.3	5-8	130	2.5

Tip

The use of compressed air containing oil significantly increases the life of the sealings on the device.

Staples, type 80




Model	Art. no.	Back width (mm)	Wire thickness (mm)	Length (mm)	Bulk buying (pc.)
KL 80/06 CNK/3000	DGKC420003	12.8	0.9x0.7	6	3,000
KL 80/08 CNK/3000	DGKC420004	12.8	0.9x0.7	8	3,000
KL 80/10 CNK/3000	DGKC420005	12.8	0.9x0.7	10	3,000
KL 80/12 CNK/3000	DGKC420006	12.8	0.9x0.7	12	3,000
KL 80/14 CNK/3000	DGKC420007	12.8	0.9x0.7	14	3,000
KL 80/16 CNK/3000	DGKC420008	12.8	0.9x0.7	16	3,000

CNK – Chisel tip; nickel-plated

Staples, type 90

Model	Art. no.	Back width (mm)	Wire thickness (mm)	Length (mm)	Bulk buying (pc.)
KL 90/15 CNKH/2000	DGKC420022	5.7	1.25x1	15	2,000
KL 90/20 CNKH/2000	DGKC420024	5.7	1.25x1	20	2,000
KL 90/25 CNKH/2000	DGKC420027	5.7	1.25x1	25	2,000
KL 90/28 CNKH/5000	DGKC420029	5.7	1.25x1	28	5,000
KL 90/30 CNKH/2000	DGKC420030	5.7	1.25x1	30	2,000
KL 90/30 CV2AH/5000	DGKC421030	5.7	1.25x1	30	5,000
KL 90/35 CNKH/2000	DGKC420034	5.7	1.25x1	35	2,000
KL 90/40 CNKH/2000	DGKC420035	5.7	1.25x1	40	2,000


CNKH – Chisel tip; nickel-plated; resin-coated
CV2AH – Chisel tip; stainless steel; resin-coated



Staples, type 114

Model	Art. no.	Back width (mm)	Wire thickness (mm)	Length (mm)	Bulk buying (pc.)
KL 114/30 CNKH/20000	DGKC430021	10.8	1.6x1.4	30	20,000
KL 114/35 CNKH/10000	DGKC430022	10.8	1.6x1.4	35	10,000
KL 114/40 CNKH/10000	DGKC430023	10.8	1.6x1.4	40	10,000
KL 114/45 CNKH/10000	DGKC430024	10.8	1.6x1.4	45	10,000
KL 114/50 CNKH/10000	DGKC430025	10.8	1.6x1.4	50	10,000
KL 114/65 CNKH/10000	DGKC430026	10.8	1.6x1.4	65	10,000


CNKH – Chisel tip; nickel-plated; resin-coated



Staples, type 347

Model	Art. no.	Back width (mm)	Wire thickness (mm)	Length (mm)	Bulk buying (pc.)
KL 347/10 CNK/2500	DGKC430003	4.55	0.9x0,7	10	2,500
KL 347/16 CNK/2500	DGKC430006	4.55	0.9x0,7	16	2,500
KL 347/20 CNK/2500	DGKC430008	4.55	0.9x0,7	20	2,500
KL 347/25 CNKH/2500	DGKC430010	4.55	0.9x0,7	25	2,500

CNK – Chisel tip; nickel-plated
CNKH – Chisel tip; nickel-plated; resin-coated



Staplers and nail guns

Multi-purpose nail driver



- Compact, lightweight design for easy operation and fatigue-free work
- Flexible design compatible with both SN pan-head nails (16-50 mm) and type 90 staples (13-40 mm)
- Simple and precise adjustment of the staple insertion depth with tool-free depth setting
- Rubber handle reduces vibrations and provides insulation against the cold

- ✓ Contact fuse reduces the risk of accidents
- ✓ In a Systainer with 1000 SN pan-head nails, length 40 mm, 2000 type 90 staples, length 30 mm

Model	Art. no.	Air requirement (l/stroke)	Working pressure (bar)	Magazine capacity	Weight (kg)
KNG 40/50 SYS	DGKD300046	1.1	5-8	100	1.1

Pan-head nailer



- Compact, lightweight design for easy operation and fatigue-free work
- Simple and precise adjustment of the staple insertion depth with tool-free depth setting
- Rubber handle reduces vibrations and provides insulation against the cold

- ✓ For SN pan-head nails, length 16-50 mm
- ✓ Contact release for quick, safe working progress
- ✓ In a Systainer with safety glasses, 5000 SN pan-head nails, length 30 mm

Model	Art. no.	Air requirement (l/stroke)	Working pressure (bar)	Magazine capacity	Weight (kg)
SNG-SK 50 SYS	DGKD300067	1.1	5-8	100	1.26

SN pan-head nails



Model	Art. no.	Wire thickness (mm)	Length (mm)	Packaging unit (pc.)
SN 113 NK/1000	DGKC520011	0.9x1.2	13	1,000
SN 116 NK/1000	DGKC520012	0.9x1.2	16	1,000
SN 116 NK/5000	DGKC520002	0.9x1.2	16	5,000
SN 120 NK/1000	DGKC520013	0.9x1.2	20	1,000
SN 120 NK/5000	DGKC520003	0.9x1.2	20	5,000
SN 125 NK/1000	DGKC520014	0.9x1.2	25	1,000
SN 125 NK/5000	DGKC520004	0.9x1.2	25	5,000
SN 130 NK/1000	DGKC520015	0.9x1.2	30	1,000
SN 130 NK/5000	DGKC520005	0.9x1.2	30	5,000
SN 130 V2A/5000	DGKC521005	0.9x1.2	30	5,000
SN 135 NK/5000	DGKC520006	0.9x1.2	35	5,000
SN 140 NK/5000	DGKC520008	0.9x1.2	40	5,000
SN 150 NK/5000	DGKC520010	0.9x1.2	50	5,000

NK – nickel-plated
V2A – stainless steel

Pin nailer

- Small diameter pin nails for securing decorative profiles, window beads, ornaments, etc. almost invisibly
- Narrow front plate ideal for machining extremely narrow, delicate workpieces
- Compact, lightweight design for easy operation and fatigue-free work
- Rubber handle reduces vibrations and provides insulation against the cold

In a Systainer with safety glasses



Typ	Art.-Nr.	Luftbedarf (l/Hub)	Arbeitsdruck (bar)	Magazin-kapazität	Gewicht (kg)
PN 25 SYS	DGKD300068	0.3	4-7	102	0.95

Tip

Clean the magazine with compressed air from time to time. Never clean with fluids or oils because the pin nail may become stuck.

Pin nails

Typ	Art.-Nr.	Drahtstärke (mm)	Länge (mm)	Verpackungseinheit (Stück)
PN 15-0,6 NK/10000	DGKF440130	0.64	15	10,000
PN 18-0,6 NK/10000	DGKF440131	0.64	18	10,000
PN 22-0,6 NK/10000	DGKF440132	0.64	22	10,000
PN 25-0,6 NK/10000	DGKF440133	0.64	25	10,000

NK – nickel-plated



T-nail type TN

Model	Art. no.	Wire thickness (mm)	Length (mm)	Packaging unit (pc.)
TN 22/60 NK/10000	DGKF440016	2.18	60	10,000
TN 22/64 NK/10000	DGKF440017	2.18	64	10,000

NK – nickel-plated



Tip

Select the nail length so that a third of the nail is driven into the material and two thirds is driven into the backing material.

Staplers and nail guns

Round-head nailer




- Compact, lightweight design for easy operation and fatigue-free work
- Simple changeover between contact and single release with adaptable trigger
- Rubber handle reduces vibrations and provides insulation against the cold



Contact fuse reduces the risk of accidents

Model	Art. no.	Air requirement (l/stroke)	Working pressure (bar)	Magazine capacity	Weight (kg)
RNG-RN 90	DGKD300071	2.9	5-8.5	63	3.3

Strip nail type RN



Model	Art. no.	Nail angle (°)	Wire thickness (mm)	Length (mm)	Packaging unit (pc.)
RN 29/65 BKH/3000	DGKF440021	21	2.9	65	3,000
RN 31/70 BKH/3000	DGKF440027	21	3.1	70	3,000
RN 31/80 BKH/3000	DGKF440024	21	3.1	80	3,000
RN 31/90 BKH/3000	DGKF440025	21	3.1	90	3,000

BKH – Blank; geharzt

Tip

Select the nail length so that a third of the nail is driven into the material and two thirds is driven into the backing material.